

三菱重工業エアコン〔天吊形〕			冷媒 R410A	
形 式		セット形式 FDEP1121C		
		室内ユニット FDEP1121		室外ユニット FDCP1121C
				リモコン RC-D2
電 源			――― 3相 200V 50/60Hz	
能 力		kW	冷 房	
			10.0 / 11.2	
消 費 電 力		kW	3.30 / 3.93	
運 転 電 流		A	11.1 / 12.0	
力 率		%	86 / 95	
始 動 電 流		A	82 / 72	
外形寸法	本体	mm	250 × 1,620 × 690	1,050×920×340
高さ×巾×奥行			―――	
パ ネ ル 色 (マンセル)			パ ーホワイト (N8.5 近似)	ホ ーホワイト (2.5Y7.5/1 近似)
製 品 質 量		kg	46	82
送 風 装 置	風 量	m ³ /min	急：26 強：23 弱：21	64／66
	モータ出力	W	40×2	40×2
	機外静圧	Pa	0	―――
圧縮機用電動機出力		kW	―――	3
補 助 電 熱 器		kW	オ ー ション:2.0～2.3 (PTC)	―――
冷 媒 配 管	液配管	mm	室内接続φ9.52(7㍓) 配管φ9.52x0.8 室外接続φ9.52(7㍓)	
	ガス配管		φ15.88(7㍓) φ15.88x1.0 φ15.88(7㍓)	
	長さ制限	m	50以内	
	高さ制限		30以内 (室外ユニットが下の場合は 15以内)	
	冷 媒 量		R410A 出荷時 3.9kg(室外) 追加量:40g/m 但し30m以内は不要(チャージレス)	
騒 音 値		dB(A)	急：42 強：41/40 弱：39/38	50
法定冷凍能力		トン	1.24／1.49	
そ の 他			高圧ガス保安法に基づく手続きは、不要	
◆本機は、オゾン層破壊係数ゼロの冷媒＜R410A＞を使用しております。				
(1)冷房能力および電気特性は、適正冷媒量において日本工業規格(B8615)条件により運転した値です。				
(2)騒音値は、日本工業規格(B8616)に準拠し反響の少ない無響室にて測定した値です。				
実際に部屋に据え付けた場合は、周囲の騒音や部屋の反響を受け表示値より大きくなるのが普通です。				